REYAX
TECHNOLOGY CORPORATION, LTD

14-MAR-2018 56312E30

RYAFxxx Series

433/470/868/915 MHz SMA External Antenna

Datasheet

RYAF433 SPECIFICATION

Item	Min.	Typical	Max.	Unit	Condition
Frequency Range	425	433	441	MHz	
V.S.W.R		<=1.8			
Input Impedance		50		ohm	
Antenna Gain	4.3	5	5.7	dB	

RYAF470 SPECIFICATION

Item	Min.	Typical	Max.	Unit	Condition
Frequency Range	462	470	478	MHz	
V.S.W.R		<=1.8			
Input Impedance		50		ohm	
Antenna Gain	5.3	6	6.7	dB	

RYAF868 SPECIFICATION

Item	Min.	Typical	Max.	Unit	Condition
Frequency Range	860	868	873	MHz	
V.S.W.R		<=1.8			
Input Impedance		50		ohm	
Antenna Gain	4.3	5	5.7	dB	

RYAF915 SPECIFICATION

Item	Min.	Typical	Max.	Unit	Condition
Frequency Range	902	915	928	MHz	
V.S.W.R		<=1.8			
Input Impedance		50		ohm	
Antenna Gain	4.3	5	5.7	dB	

Copyright © 2018, REYAX TECHNOLOGY CO.,LTD.

DIMENSIONS

ORDER DETAILS

Ordering No.	Frequency Range
RYAF433	425-441MHz
RYAF470	462-478MHz
RYAF868	860-873MHz
RYAF915	902-928MHz

REYAX
TECHNOLOGY CORPORATION, LTD

Taiwan: sales@reyax.com
China: sales@reyax.com.cn
http://www.reyax.com

Copyright © 2018, REYAX TECHNOLOGY CO.,LTD.